

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 2002-027374

(43)Date of publication of application : 25.01.2002

(51)Int.Cl.

H04N 5/765

H04N 5/781

G06K 17/00

G06K 19/07

G06K 19/00

G11B 27/00

G11B 27/10

H04N 5/78

(21)Application number : 2000-200376

(71)Applicant : SONY CORP

(22)Date of filing : 30.06.2000

(72)Inventor : SHIMIZU RYOICHI

(54) APPARATUS AND METHOD FOR INFORMATION RECORDING AS WELL AS APPARATUS, METHOD AND SYSTEM FOR INFORMATION PROCESSING

(57)Abstract:

PROBLEM TO BE SOLVED: To prevent the trouble such as generation of a noise caused by sending image signals of wrong systems to edit by a method wherein meta-data related to an image signal is detected precisely and quickly before starting, e.g. editing.

SOLUTION: When the image signal is recorded on a magnetic tape 30, meta-data related to the recording system of the image signal is recorded in a memory tag 37. On the basis of the meta-data which is read out from the memory tag 37, a setting regarding an image signal inside an editing device 74 is controlled, and a warning is generated when the recording frequency of the image signal to be edited does not agree with a data bit rate.

